





Premium Features In KINGQUAD Style

Comfort, control, power and convenience - all in the KINGOUAD style. Fuel-injected 493cm³ powerplant ready with responsive output throughout the rev range along with strong top-end power. A host of premium features. Available with a lightweight, compact and effective electric power steering.



Photo: KINGOUAD 500AXi 4x4

■ Compact and lightweight electric power steering delivers lighter steering in a variety of conditions to reduce rider fatigue. It is positioned high on the vehicle to avoid water and debris. (KINGQUAD 500AXI 4x4 Power Steering only)

■ 493cm³ fuel-injected 4-valve powerplant engineered for robust output throughout the rpm range, along with strong top-end power.

Fuel injection improves throttle response and fuel efficiency, while delivering power consistently and improving engine start.

Efficient and functional fully automatic QuadMatic Continuously Variable Transmission (CVT), using a durable V-belt and centrifugal clutch.

Advanced engine-braking system helps the transmission control vehicle speed to minimize freewheel during descents.

Torque-sensing differential with three modes - 2WD, 4WD or differential-locked 4WD - easily selected with a handlebar-mounted button.

Solid Black No.2 (YLZ)

Fully independent suspension system - A-arm front and A-arm/l-beam rear - delivers superior riding comfort and versatile handling performance.

Shock absorbers at all four corners are adjustable for five different preload settings, providing maximum versatility for different loads.

Front dual hydraulic disc brakes and rear sealed oil-bathed multi-disc braking system deliver strong and consistent stopping performance.

25-inch tires with tread and sidewall character specially designed for the machine, mounted on lightweight and sturdy aluminum rims.

Gate-style drive mode selector lever lets the rider easily and securely select between low, high, neutral or reverse setting

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued

without notice. Please inquire at your local dealer for details of any such changes Always wear a helmet, eye protection and protective clothing. Enjoy riding safely. Read your Owner's Manual carefully. PRINTED IN JAPAN KINGQUAD 500AXI 4x4/Power Steering (LT-A500X/XZ/XP/XPZ) L4 Leaflet 99999-A3106-141 MAY'13 SUZUKI MOTOR CORPORATION

akatsuka-cho, Minami-ku, Hamamatsu City, Japan 432-8611 www.globalsuzuki.com





Full floorboards with drain holes



12V DC power outlet

Suzuki's exclusive T-shaped seat, designed for all-day comfort and easier body-weight transition during sporty trail rides

Fuel tank positioned below the seat helps keep the machine's weight center low. The tank's ratcheting gas cap is easy to tighten.

Standard equipment including a tow hitch and a sealed 12V accessory outlet

Two storage compartments: one easily accessible under the rear fender, and another with a spin-off top on the right front fender.

Complete gauge package, including a speedometer, odometer, separate trip meter, gear and differential displays, fuel gauge, clock and more.

ATV SAFETY INFORMATION

The Suzuki KINGQUAD 500AXi 4x4/Power Steering may be used only by those aged 16 and older. ATVs can be hazardous to operate. For your safety, always wear a helmet, eye protection and protective clothing. Always avoid paved surfaces. Never ride on public roads. Never carry passengers or engage in stunt riding. Riding and alcohol or other drugs don't mix. Avoid excessive speed. Be extra careful on difficult terrain. Read your Owner's Manual carefully

Specifications

SOHC

10.0:1

4-stroke, 1-cylinder, liquid-cooled,

CVT, 2-Speed forward with reverse

2135 mm (84.1 in) / 2165 mm (85.2 in)

1250 mm (49.2 in) / 1250 mm (49.2 in)

1245 mm (49.0 in) / 1285 mm (50.6 in)

1285 mm (50.6 in) / 1285 mm (50.6 in)

260 mm (10.2 in) / 260 mm (10.2 in)

920 mm (36.2 in) / 920 mm (36.2 in)

Independent, double wishbone, coil spring, oil-damped

Independent, double wishbone. coil spring, oil-damped

307 kg (676 lbs) / 302 kg (666 lbs)

493 cm3 (30.1 cu. in)

87.5 mm x 82.0 mm

Engine Displacement Bore x Stroke **Compression Ratio** Transmission **Overall Length** LT-A500X/XP LT-A500X/XP **Overall Width Overall Height** LT-A500X/XP Wheelbase LT-A500X/XP Ground Clearance LT-A500X/XP Seat Height LT-A500X/XP Curb Mass LT-A500X/XP Suspension Front Rear Brakes Front

Engine Type

Disc, twin Rear Sealed oil-bathed multi-disc AT25x8-12^{☆☆}, tubeless Front AT25x10-12☆☆. tubeless Rear Ignition Type Electronic ignition (CDI) 17.5 L (4.6 US gal) Fuel Tank Capacity

Colors

Photo : KINGOUAD 500AXi 4x4 Power Steering

Tires





Flame Red (YT9)

Champion Yellow No.2 (YU1)





Metalic Mat Royal Red (PGR) Photo : LT-A500XZ

Great Blue (YPW)

True Timber XD3 (PHW) Metallic Mat Royal Gray (PNB) Photo : LT-A500XPZ Photo : LT-A500XPZ

